

<b>DISTANCE:</b>	<b>36 FEET</b>	<b>VOLUME:</b>	<b>28.6 mL</b>
<b>RATIO:</b>	<b>1.58:1</b>	<b>FORWARD:</b>	<b>22.8 mL</b>
<b>DROP BRUSH:</b>	<b>35 FEET</b>	<b>REVERSE:</b>	<b>5.8 mL</b>
<b>TANKS:</b>	<b>ICE</b>	<b>PUMP:</b>	<b>50<math>\mu</math>L</b>



**FORWARD LOADS DATA**

#	START	STOP	LOADS	MICS	SPEED	BUFF	TANK	DISTANCE	T.OIL
1	2L	2R	4	50	14	3	B-Ice	0 → 6	7,400
2	4L	4R	3	50	18	3	B-Ice	6 → 13	4,950
3	5L	5R	3	50	18	3	B-Ice	13 → 21	4,650
4	6L	6R	4	50	18	3	B-Ice	21 → 31	5,800
5	2L	2R	0	50	22	3	B-Ice	31 → 36	0

**REVERSE LOADS DATA**

#	START	STOP	LOADS	MICS	SPEED	BUFF	TANK	DISTANCE	T.OIL
1	2L	2R	0	50	30	3	B-Ice	35 → 15	0
2	7L	7R	2	50	18	4	B-Ice	15 → 10	2,700
3	5L	5R	2	50	14	4	B-Ice	10 → 6	3,100
4	2L	2R	0	50	14	4	B-Ice	6 → 0	0

**THIS PATTERN IS DESIGNED FOR:**  
 VARIABLE BUFFER SPEEDS | REVERSE DROP BRUSH  
 This pattern may require adjustments if using a lane machine that does not have these features

